

Material Safety Data Sheet

1.Identification of Substances/Preparation and of the Company/undertaking.

· Product details

· Trade name: Butyl acrylate · Manufacturer/Supplier:

Jay Overseas Pvt.Ltd. 402, Shopper Plaza-IV,

Opp.Lal Bunglow,

C.G. Road, Navrangpura,

Ahmedabad-380 009

Ph:+91 79-66622278 to 92 Fax:+91 79-66622280 /90

E-Mail Id: info@jayoverseas.com

· Further information obtainable from: Product safety department.

2. Composition/Information on ingredients.

· Chemical characterization:

· CAS No. Description

141-32-2 n-butyl acrylate

· Identification number(s)

· EINECS Number: 205-480-7

· EU Number: 607-062-00-3

3. Hazards Identification.

· Hazard description:



Xi Irritant

· Information concerning particular hazards for human and environment:

R 10 Flammable.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 43 May cause sensitisation by skin contact.

4. First Aid Measures.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- $\cdot \textit{After skin contact:} \ \textit{Immediately wash with water and soap and rinse thoroughly}.$
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

5. Fire-Fighting Measures.

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

6.Accident Release Measures.

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

7. Handling & Storage.

- · Handling:
- · Information for safe handling: No special requirement
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

8.Exposure Control/Personal Protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

141-32-2 n-butyl acrylate

55 mg/m³, 10 ppm
SEN
Short-term value: 53 mg/m³, 10 ppm
Long-term value: 11 mg/m³, 2 ppm
Short-term value: 26 mg/m³, 5 ppm
Long-term value: 5 mg/m³, 1 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use

self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and

varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9. Physical and Chemical Properties.

· General Information

Form: Fluid
Colour: Colourless

Odour: Fruit-like

· Change in condition

Melting point/Melting range: $-64.6^{\circ}C$

Boiling point/Boiling range: 145°C

· Flash point: 37°C

· Ignition temperature: 275°C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixturesare possible.

· Explosion limits:

Lower: 1.2 Vol % **Upper:** 8 Vol %

· Vapour pressure at 20°C: 5.3 hPa

· Density at 20°C: 0.8898 g/cm3

· Solubility in / Miscibility with

water at 20°C: 1.4 g/l

10.Stability and Reactivity.

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11. Toxilogical Information.

· Acute toxicity:

· LD/LC50 values relevant for classification:

Dermal-----2000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.

12. Ecological Information.

· General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13.Disposal Consideration.

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.Transport Inforamtion.

- · Land transport ADR/RID (cross-border)
- · ADR/RID class: 3 Flammable liquids.



· Danger code (Kemler): 39 · UN-Number: 2348

· Packaging group: III · Hazard label: 3

· Description of goods: 2348 BUTYL ACRYLATES, STABILIZED

· Maritime transport IMDG:



· IMDG Class: 3 · UN Number: 2348

· Label 3

· Packaging group: III · EMS Number: F-E,S-D

· Proper shipping name: BUTYL ACRYLATES, STABILIZED

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 2348

· Label 3

· Packaging group: III

· Proper shipping name: BUTYL ACRYLATES, STABILIZED

15. Regularity Information.

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xi Irritant

· Risk phrases:

10 Flammable.

36/37/38 Irritating to eyes, respiratory system and skin.

- 43 May cause sensitisation by skin contact.
- · Safety phrases:
- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.

16.Other Information.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.